R49003046 SOCKET SET 1/4"

85°



















46 pieces

- Coupler based on DIN 3120 A 6.3, ISO 1174, with ball lock
- > Square drive as per DIN 3120 C 6.3, ISO 1174, with ball retention groove
- 2C reversible ratchet 1/4": lever for reversing clockwise/anticlockwise direction, push-button release, fine-toothed, oval head, dual-material handle for ease in gripping, for sockets
- > Square plug-in handle 1/4": 1-component handle with female square
- **Socket 1/4", hex:** metric, short, as per DIN 3124, ISO 2725
- > Screwdriver bit socket 1/4", for hex screws: with pressed-in, phosphated pin
- > Screwdriver bit socket 1/4", slotted: with pressedin, phosphated pin
- > Screwdriver bit socket 1/4" PH: with pressed-in, phosphated pin

- **> Screwdriver bit socket 1/4" PZ:** with pressed-in, phosphated pin
- Screwdriver bit socket 1/4" TX: with pressed-in, phosphated pin
- > Socket extension 1/4"
- > Flexible socket extension 1/4"
- > Sliding T-bar with slider 1/4": as per DIN 3122, ISO 3315
- > Universal joint 1/4": screwed-on joint, acc. to DIN 3123 - C 6.3
- **> Bit adaptor 1/4":** with in-hex and female square, for all bits and tools with 1/4" external hex
- Hexagon socket key set: as per DIN ISO 2936
 Chrome-vanadium steel, matt satin chrome-plated
- > For hand-operated screw work
- Plastic case in GEDORE red DesignClamp-secured tools
- Metal hinges/fastener





Code	No.	Contents	L	W	D	pieces	∆ kg €
3300052	R49003046	1/4" 2C lever reversible ratchet, fine-toothed, 72 teeth 150 mm	300	180	52	46	1.57
		1/4" square plug-in handle 165 mm					
		1/4" socket hexagon 4 4.5 5 5.5 6 7 8 9 10 11 12 13 14 25 mm					
		1/4" screwdriver bit socket in-hex 3 4 5 6 7 8 37 mm					
		1/4" screwdriver bit socket slotted 4 5.5 6.5 37 mm					
		1/4" screwdriver bit socket cross-head PH 1 2 3 37 mm					
		1/4" screwdriver bit socket cross-head PZ 1 2 37 mm					
		1/4" screwdriver bit socket TX T10 T15 T20 T25 T27 T30 T40 37 mm					
		1/4" socket extension 50 100 mm					
		1/4" flexible socket extension 150 mm					
		1/4" sliding T-bar with slider 115 mm					
		1/4" universal joint 32 mm					
		Bit adapter 1/4" sg. x 1/4" hex 25 mm					
		Hexagon socket key set 1.27 1.5 2 2.5 mm					