

INVISIBLE RUBBER PRODUCT DESCRIPTION

This water-borne coating is a highly flexible pure acrylic solution, developed to be water-resistant and non-yellowing with rust-inhibiting properties. It can be applied to virtually all surfaces. The product features a fine particle size, medium viscosity, and outstanding ultraviolet tolerance. Transparent when dry, it can be used as both a base coat and a topcoat.

APPLICATION AREAS

- Suitable on all surfaces
- Interior and exterior use
- Galvanized Surfaces
- Cement Surfaces
- Wood Surfaces
- Windows and more...

PRODUCT FEATURES

- Highly flexible pure acrylic coating
- Water-resistant
- Non-yellowing
- Milky when wet, transparent when dry
- Excellent adhesion
- UV resistant
- Easy no-mess Application properties
- Quick Drying - 2 coats can be applied in one day
- Direct application - no primer needed
- Can be used as a base and top-coat
- Rust Inhibitor

PRODUCT DATA

Physical Form	High Viscosity Liquid
Finish	Semi-Gloss (Milky when wet and clear when dry)
Equipment Cleaning	Water - Do not allow the product to dry on equipment
Spreading Rate	2m ² per 1ℓ application on 100 microns per coat. Coverage will depend on the porosity of surface and application method
Touch Drying	± 30 minutes depending on the humidity
Drying Time	± 7 - 14 hours depending on humidity
Thinning	Not recommended

APPLICATION DETAILS:

Mixing:	Always stir well before use with a flat paddle.
Application Method:	Brush or roller
Thinning:	This product is ready for use un-thinned
Cleaning:	Application equipment clean-up is with clean tap water.
Application:	<p>For Brush or Roller Application:</p> <ul style="list-style-type: none"> • Apply 2 coats of Invisible Rubber to achieve proper penetration and allow to dry 60 - 90 minutes between coats, depending on temperature • Porous surfaces and coastal areas may require a third coat to ensure surfaces are properly coated.

SURFACE PREPARATION

Steel and Galvanized Structures	<ul style="list-style-type: none">• Remove all rust with a good-quality Rust Remover, scrub, and rinse thoroughly with water• Remove dust, oil, grease, and other foreign material with a good-quality Degreaser.• Ensure the surface is sound with 60 - 90 minutes between coats, depending on temperature.
Unpainted & Weathered	<ul style="list-style-type: none">• Make sure the old paint coating is firm and solid• Remove all loose, flaking, and bubbling paint• Treat rusted areas with a good quality Rust Remover using a wire brush, hard bristle brush, or broom. Wash off with water.• Remove dust, oil, grease, and other foreign material with a good-quality Degreaser.• Wash thoroughly with water. Allow to dry.• Ensure that the surface is sound and dry before painting• Apply two coats of Invisible Rubber with 60 - 90 minutes between coats, depending on temperature.
Fibre-Cement, Cement Tiles and Granular Tiles	<ul style="list-style-type: none">• Remove all dust, dirt and loose granules, friable and powdery material with a high-pressure water jet or scrub down with a hard bristle or wire brush with water.• Ensure that the surface is sound and dry before painting.• Apply two coats of Invisible Rubber with 60 - 90 minutes between coats, depending on temperature.

COLOUR RANGE AND QUANTITIES

- This product is available in clear only
- Available in 1ℓ, 5ℓ and 20ℓ

PRECAUTIONS

- This product is not flammable, contains no toxic substances and only low levels of VOC (EU Regulations)

DISCLAIMER

- Eco Advanced™ cannot be held liable if the product fails due to improper surface preparation or application.