



Address: 5 Ixia Street, Durbanville, 7550

Company Reg: 2017/051218/07

VAT NR: 4500299013

Contact: 087 700 5371

TECHNICAL DATA SHEET

Product Name: PowerBond Max Strength Waterproof Sealant Tape

Size: 1.5M

Colour: Transparent

Temperature Resistance: -10°C to +40°C

Pressure Resistance: Withstands 8 Bar Water Pressure & 6 Bar Air Pressure

Compatibility: Compatible with PVC, Acrylic, Metal, Steel, Copper, Aluminum, Wood, Ceramic, Porcelain, Tile, Glass, Rubber, Fiberglass, Stucco, Plaster, Stone, Cement, Concrete, Drywall, EPDM Roofs, Fabrics, Vinyl, and more.

USES:

- Sealing water and air leaks
- Repairing cracks, gaps, and holes in various surfaces
- Sealing air ducts, pipes, hoses, water tanks, and more
- Suitable for both indoor and outdoor applications
- Can be applied underwater and used to seal air and cracks

INSTRUCTIONS FOR USE:

1. Ensure the surface is clean before applying the tape.
2. Cut the desired length of tape using scissors or a knife.
3. Remove the backing paper from one side of the tape.
4. Apply the tape to the affected area, overlapping the edges by at least 1 cm.
5. Smooth out any air bubbles or wrinkles with your fingers or a roller.
6. Firmly press the tape in place to ensure a secure bond.

STORAGE:

Store in a cool, dry place at a temperature between 5°C to 30°C. Keep away from direct sunlight and heat sources.

DISCLAIMER:

The information provided in this data sheet is based on the current state of knowledge and experience. However, the performance of the product may be affected by factors beyond our control. Users of our product should always determine the suitability of the product for their application and exercise their own judgment in proper use and handling. We assume no liability for any damage or injury arising from the use of this product.