



TECHNICAL DATA SHEET: PLASTERS, FILLERS & SKIMMERS



CEMENT OXIDE

DRY MIX COLOURED DYE

FEATURES AND BENEFITS

- Effective and easy to use dry mix
- Try our Cementitious paint formula
- Natural long-lasting colours

DIRECTIONS FOR USE

USAGE PRECAUTIONS

Read all instructions before use. Do not exceed mixing ratio of 1 part Oxide to 10 parts cement by weight as this will weaken the mix. Recommend plaster mix is 6 parts aggregate (sand plus oxide) to 1 part cement. Recommended decorative screed mix is 4 parts aggregate (sand plus oxide) to 1 part cement. These are recommended ratio's only; the use of Cement Oxides is beyond our control and Powafix cannot be held liable for damages from the use of this product. Make a small test sample and allow to dry to check final colour. To ensure colour consistency always weigh ingredients. Cement Oxides are also compatible with Powafix white cement and plaster of Paris.

MIXING INSTRUCTIONS

For plaster and cementitious paint applications thoroughly clean surfaces with Powafix Mortar Off*.

Plaster / Screeds / Paving and bricks - Premix all dry components first (cement, sand oxide). Premix Powafix Powabond* with water. Add liquid to dry mix and mix to a uniform, lump free paste.

Cementitious paint – Prepare dry mix to ratio and scale up or down as required. Thoroughly mix 10kgs Powafix white cement with 2kg Powafix Cement Oxide. Add 10L of Powafix Powabond and mix to a uniform, lump free slurry. Coverage of this mix is approximately 50m². Allow 24 hours to dry and use Powafix Hydrofix* to coat and seal.

* Use product directions displayed on respective products

STORAGE INSTRUCTIONS

Keep product upright and secure when transporting. Store product in a cool, damp free place out of reach of children. Once product has been opened fold bag over. Do not eat, drink or smoke when using product. Take off contaminated clothing and wash thoroughly after use. For disposal enquiries contact 0860254620.





TECHNICAL DATA SHEET: PLASTERS, FILLERS & SKIMMERS



SAFETY INSTRUCTIONS

Read all instructions before use. This product is a potential hazard to the eyes, skin and respiratory tracks. Use product in well ventilated areas. Keep out of reach of children. Store in a secure location. If medical advice is needed, have product packaging at hand. Use personal protection as required. Wear protective gloves. Wear eye protection. Wear a dust mask. Avoid inhalation of dust.

IF IN EYES flush with water. Seek medical attention if symptoms persist.

IF ON SKIN wash with soapy water. IF SWALLOWED do not induce vomiting and seek immediate medical attention.

Dispose of contents and packaging in accordance with all local, regional, national and international regulations. National poison centre 0861 555 777.

PRODUCT GUARANTEE

In the unlikely event that you are not totally satisfied - this product has a 12-month warranty. This warranty only includes replacement of the same product or a refund of the original purchase price. Product must be returned in its original packaging with proof of payment. This warranty excludes product failure caused by misuse or use of the product outside of recommended uses and instructions on the packaging.




PRODUCT INFORMATION

Colour	Barcode	Product Code	Pack Size	Case Size	
BLACK	6009600992047	OXI500GBL	500G	25	
	6009600992054	OXI2KGB	2KG	8	
	6009600992795	OXI40KGB	40KG	1	
BLUE	6009600992061	OXI500GB	500G	25	
	6009600992078	OXI2KGBL	2KG	10	
	6009600992450	OXI25K	25KG	1	
BROWN	6009600992085	OXI500GBR	500G	25	
	6009600992092	OXI2KGBRO	2KG	10	
	6009600992429	OXI40KGBR	40KG	1	



TECHNICAL DATA SHEET: PLASTERS, FILLERS & SKIMMERS



GREEN	6009600992108	OXI500GG	500G	25	
	6009600992115	OXI2KGGS	2KG	10	
	6009600992436	OXI25KGG	25KG	1	
RED	6009600992122	OXI500GR	500G	25	
	6009600991378	OXI2KGRS	2KG	10	
	6009600992443	OXI40KGR	40KG	1	
YELLOW	6009600991385	OXI500GY	500G	25	
	6009600991392	OXI2KGYS	2KG	10	
	6009600992467	OXI40KGY	40KG	1	

PRODUCT SPECIFICATION

Appearance	Fine Powder
Available Colours	Black, Blue, Brown, Green, Red and Yellow.
Moisture	< 3 %
Particle Size	75 µm (Blue, Brown, Green, Red & Yellow) 150 µm (Black Oxide)

ISSUE DATE: NOVEMBER 2021

The information contained on this Technical Data Sheet is, to the best of our knowledge, true and accurate. As the conditions of use are not under our control, no warranty is given or implied in respect of such information, or in respect of any recommendations or suggestions which may be made.