



TECHNICAL DATA SHEET: TIMBER TREATMENTS



FENCE DEFENCE®

PROTECTIVE TIMBER COATING

FEATURES AND BENEFITS

- Waterproofs timber against wood rot & decay
- Seals & prevents timber drying & cracking
- Low odour product suitable for interior & exterior use

DIRECTIONS FOR USE

USAGE PRECAUTIONS

Read all instructions before use. Remove all wood rot and apply only to permanently dry timber. Not suitable for timber structures being used as retaining walls. In areas susceptible to insect attack use pre-treated timber. If Fence Defence is to be used on timber below ground (anchor posts) treat with a minimum of three coats. Fence Defence coats timber to selected colour. Paint with corresponding batch numbers to ensure colour consistency. Do not paint in cold weather below 8°C or if imminent rainfall is expected. In areas affected by heavy dew do not paint after 2pm. Do not apply coating on any contaminated or unsound surface as this will affect the adhesion. Contact our technical help line on 072 396 4980 for assistance prior to painting.

SURFACE PREPARATION

Remove all loose / flaking material. Sand smooth any glossy or uneven surfaces. Thoroughly clean any surface contaminates with Powafix Sugar Soap* and Powafix Fungi fix* for algae or fungi. Treat wood rot before applying. Use Powafix Timbafix wood filler* to fill surface imperfections. Prime surface with Powafix Pink Wood Primer*.

APPLICATION INSTRUCTIONS

Stir well before use. Apply product with a brush or roller. This may increase on porous or rough surfaces. Allow 2 – 4 hours drying time between coats. Clean brushes with Powafix Solvent Based Brush Cleaner*. Product thinning is not recommended. Apply a maintenance coat every 18 months.

*Use product directions displayed on respective products

STORAGE INSTRUCTIONS

Ensure lid is tightly sealed and product stored upright. Secure product when transporting to prevent accidental spillage. Store in a cool place out of reach of children. Dispose of empty container and do not use for any other purpose. Do not dispose into common waste system contact 0860 254 620 for disposal information. Discard product 18 months after batch date.





TECHNICAL DATA SHEET: TIMBER TREATMENTS



SAFETY INSTRUCTIONS



May cause an allergic skin reaction

Read all instructions before use. Replace lid when not in use. Use product in well ventilated areas. If medical advice is needed, have product packaging at hand. Do not eat or drink when using product. Use personal protection as required. Wear protective gloves. Wear eye protection. Wear a dust mask. Avoid inhalation of dust.

IF IN EYES Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Seek medical attention if symptoms persist.

IF ON SKIN Take off immediately all contaminated clothing and wash before reuse. Wash skin with soapy water.

Seek medical attention if symptoms persist. **IF SWALLOWED** Do not induce vomiting and seek immediate medical attention.

Dispose of contents and packaging in accordance with all local, regional, national and international regulations.

National poison centre 0861 555 777.

PRODUCT GUARANTEE

In the unlikely event that you are not totally satisfied - this product has a 12-month warranty. This warranty only includes replacement of the same product or a refund of the original purchase price. Product must be returned in its original packaging with proof of payment. This warranty excludes product failure caused by misuse or use of the product outside of recommended uses and instructions on the packaging.

PRODUCT INFORMATION

Colour	Barcode	Product Code	Pack Size	Case Size	
BROWN	6009600996540	FEND1LBR	1LT	6	
	6009600996557	FEND5LBR	5LT	2	
BLACK	6009600996366	FEND1L	1LT	6	
	6009600996199	FEND5L	5LT	2	
GREEN	6009600996571	FEND1LGR	1LT	6	
	6009600996588	FEND5LGR	5LT	2	



More than just a product.

BRAND



QUALITY



SERVICE



VALUE



TECHNICAL DATA SHEET: TIMBER TREATMENTS



PRODUCT SPECIFICATION

Appearance	Liquid
Colours Available	Black , Brown and Green
Viscosity	90 – 100 ku
Density	1.28 – 1.34 kg/l
pH	8.5 – 9.5

ISSUE DATE: NOVEMBER 2021

The information contained on this Technical Data Sheet is, to the best of our knowledge, true and accurate. As the conditions of use are not under our control, no warranty is given or implied in respect of such information, or in respect of any recommendations or suggestions which may be made.