




TECHNICAL DATA SHEET: PUTTY & ADHESIVES



MULTI PURPOSE GLAZING PUTTY

WEATHER RESISTANT

FEATURES AND BENEFITS

- Suitable for use on both steel and wood surfaces
- Linseed Oil enriched formula with increased UV resistance
- Once dry putty can be painted or varnished



DIRECTIONS FOR USE

SURFACE PREPARATION

Read all instructions before use. Remove all loose glass, dust & flaking particles. Sand smooth any high gloss surfaces and treat any rust with Powafix Rust Mate*. Clean surfaces with Powafix Sugar Soap*. Teak putty is colored to suit wooden window frames. Both products are suitable for use on steel and wood surfaces. Wooden window frames must be sealed before using Powafix Multi-Purpose Putty. Steel window frames must be coated with a suitable primer prior to glazing. Powafix Raw or Boiled Linseed Oil* can be used to seal timber. Prime dried white putty with Universal Undercoat before painting. Alkyd timber varnish can be applied directly to dried teak putty.

500g of Putty will glaze approximately 1 meter of window frame.
1kg of putty will glaze approximately 2 meters of window frame.
2kg of putty will glaze approximately 4 meters of window frame.
5kg of putty will glaze approximately 10 meters of window frame.
20kg of putty will glaze approximately 40 meters of window frame.

APPLICATION INSTRUCTIONS

Work putty by hand to make it smooth and easy to use. Before placing the glass in press putty into the back section of the window frame. Shape & smooth with a putty knife. Place in the glass and ensure it is well supported and secure. Roll putty into a sausage and apply around the frame on the outside of the glass & onto the metal or wooden window frame, smoothing with a putty knife. Putty gradually hardens over 7-14 days (weather dependant). Once surface dry coat as required.



More than just a product.

BRAND



QUALITY




SERVICE



VALUE



TECHNICAL DATA SHEET: PUTTY & ADHESIVES



USAGE PRECAUTION

Do not mix paraffin or any other solvent with Powafix Putty. Putty can be softened by adding a small amount of Powafix Raw Linseed oil.

*Use product directions displayed on respective products

STORAGE INSTRUCTIONS

Fold over or seal bag when not in use. Secure product when transporting to prevent accidental spillage. Store in a cool place out of reach of children. Dispose of empty bag and do not use for any other purpose. Discard product 18 months after batch date. Do not dispose into common waste system contact 0860254620 for disposal information.

SAFETY INSTRUCTIONS

Read all instructions before use. Use product within well-ventilated areas. If medical advice is needed, have product packaging at hand. Use personal protective equipment as required. Wear protective gloves. Wear eye protection. Wear a dust mask. Avoid inhalation of dust.

IF IN EYES flush with water. Seek medical attention if symptoms persist.

IF ON SKIN wash with soapy water.

IF SWALLOWED do not induce vomiting and seek immediate medical assistance.


Dispose of contents and packaging in accordance with all local, regional, national, and international regulations. Nation poison centre: 0861 555 777

PRODUCT GUARANTEE



In the unlikely event you are not totally satisfied – this product has a 12-month warranty. This warranty only includes replacement of the same product or a refund of the original purchase price. Product must be returned unaltered, in its original packaging with proof of purchase. This warranty excludes product failure caused by misuse of product outside of recommended uses and instructions on the packaging.



TECHNICAL DATA SHEET: PUTTY & ADHESIVES



PRODUCT INFORMATION

Colour	Barcode	Product Code	Pack Size	Case Size	
WHITE	6009600991002	PUT50GW	500G	48	
	6009600992931	PUT1KGWS	1KG	24	
	6009600991019	PUT2KGW	2KG	12	
	6009600992870	PUT5KGW	5KG	5	
	6009600992405	PUT20KGW	20KG	1	
TEAK	6009600991927	PUT500GTS	500G	48	
	6009600992924	PUT1KGTS	1KG	24	
	6009600992917	PUT2KGTS	2KG	12	
	6009600992887	PUT5KGT	5KG	5	
	6009600992498	PUT20KGT	20KG	1	

PRODUCT SPECIFICATION

Appearance	Oily Paste
Colour	White or Teak
Drying / hardening Time	14 -21 days

ISSUE DATE: NOVEMBER 2021

The information contained on this Technical Data Sheet is, to the best of our knowledge, true and accurate. As the conditions of use are not under our control, no warranty is given or implied in respect of such information, or in respect of any recommendations or suggestions which may be made.