



**RUBBER
COATING
MANUFACTURING**

TECHNICAL DATA SHEET

PRODUCT CODE: PP001

RCM PREP AND PAINT

COMPILED DATE: 21 JUL 23

REVISE DATE: 21 JUL 25

PRODUCT DISCRPTION

Prep and Paint consists out of two products in different bags, packed in one drum. Low sheen multi purpose waterproofing coating and All purpose roof coating.

INTENDED APPLICATIONS

Waterproofing of most building substrates, can be used with the geo-textile supplied (two coats). Paint the roof area with the All purpose roof coating that is supplied afterwards.

PRODUCT FEATURES

UV resistant and reflective
Superior elongation properties
Easy to applicate and clean with no thinning
Superior adhesion to most building materials
Environmentally friendly with no solvents
Can be used with or without geotextile membranes
Low odour and safe for harvesting of water

TECHNICAL DATA

Revert to MSDS sheets of: **Rubber Coating Manufacturing Leak Block**
Rubber Coating Manufacturing All Purpose Coating.

APPLICATION DIRECTIVE

Mixing and Thinning:

Single component, stir well before use. Do not dilute.

Application: PREP PHASE

Use LEAK BLOCK bag 1 to close and treat all waterproofing issues on the roof. Close all lap and cross joints, flashings, parapets and ridging's (use in conjunction with geo-textile supplied). Use LEAK BLOCK bag 2 to apply second coat to the areas that were coated with bag one. Make sure this is done after the first coat is dry. An third coat must be applied in areas where geo-textile were used.

Application: COAT PHASE

After the the PREP phase is done and properly cured, proceed with bag 1 of the ALL PURPOSE COATING. Shake and stir well and apply with a brush or roller to the intended area. Bag 2 is intended for the second coat that can only be applied once the first coat is completely dry.

Coverage:	LEAK BLOCK: 0.8 to 1 L per square meter, dependant on: Substrate (Profile and porosity) and application (with or without geotextile) ALL PURPOSE COATING: 3 to 4 square meter per L, dependant on: Substrate (Profile and porosity) and application.
Environment:	10 to 30 Deg C, Max R Humidity 85%
Drying time before overcoat:	3 Hours @23 Deg C, R Humidity 50%
Substrate:	Clean thoroughly, remove old unstable paint and waterproofing materials. Treat all rusted areas if applicable. Substrate must be dry.
Maintenance coats:	3 - 4 Years

TRANSPORTATION AND STORAGE

Transport:	Classified as non-hazardous
Store:	Store away from severe cold, heat and direct sun.

PACKAGING

Standard:	<p>20L Bucket</p> <p>Rubber Coating Manufacturing Leak Block 8Kg (split in 2 bags) Rubber Coating Manufacturing All Purpose Coating 8L (split in 2 bags) Geo-textile: 200mm x 10m Brach: 125mm</p>
------------------	---

SAFETY PRECAUTIONS

Although the product is non-hazardous, caution should be taken during application and storage. Keep container closed properly and away from children. Avoid contact with eyes, do not ingest. If ingested, drink plenty of water or milk, seek medical attention immediately. Refer to MSDS for complete information.

These recommendations are made as a result of testing and experience, it is believed to be true and in good faith. These directives do not imply any guarantee as the application and surface preparation methods is not within our control.



**RUBBER
COATING
TECHNOLOGIES**
WATER PROOFING AT IT'S BEST

MARIUS VAN DER WESTHUIZEN

Cell: 083 262 6432
Office: 041 484 1569
Email: marius@rubbercoating.co.za
Web: www.rubbercoating.co.za

ENVIRONMENTALLY SAFE, NON - HAZARDOUS PROTECTIVE COATINGS



**RUBBER
COATING
MANUFACTURING**
PTY LTD



MATERIAL SAFETY DATA SHEET

PRODUCT CODE: PP001

RCM PREP AND PAINT

COMPILED DATE: 21 JUL 23

REVISE DATE: 21 JUL 25

1. PRODUCT AND SUPPLIER IDENTIFICATION

Manufacturer: Rubber Coating Manufacturing Pty(Ltd)
Address: 62 Paterson rd., North End, Port Elizabeth, Eastern Cape, RSA
Contact details: 27 41 484 1569
marius@rubbercoating.co.za
Product use: Waterproofing Coating
Technical nature: Pure Acrylic Co Polymer based emulsion used for a waterproofing and coating

2. HAZARD IDENTIFICATION

Main Hazard: No great risk to health SAPMA rating 4 minimal
Contact Hazard
Skin: Cat 2, may cause slight irritation
Eye: Cat 2, may cause slight irritation
Acute Toxicity
Inhalation: No Data, Not Classified
Oral: Cat 2, may cause slight irritation
Dermal: No Data available
Carcinogenicity: No Data available
Flammability: Non Flammable (Water based)

3. COMPOSITION INFORMATION

	CAS:	W/W%
Acrylic Polymer	9003-63-840-60	40-60
Calcium Carbonate	1317-65-3	5-15
Pigment	N/A	1-8
Water	7732-18-5	20-30

4. FIRST AID MEASURES

Skin: Wash with water and dry
Eye: Rinse with water
Inhalation: Fresh Air
Oral: Rinse with water, if vomiting occurs naturally seek medical assistance

5. FIRE FIGHTING MEASURES

Extinguishing Media: Foam, CO2 or dry powder.
Hazard Contribution: Not flammable

6. ACCIDENTAL RELEASE MEASURES

PPE: Gloves,
Spill and Clean up method: Clean with water and absorbing materials, disghard in accordance with local regulations
Environmental precaution: Contain, make sure that the product is not washed into pools, streams or sewer.

7. HANDLING AND STORAGE

Store in accordance with local regulations. Store away from severe cold, heat and direct sun. Keep container sealed and away from children.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Engineering Controls:	Adequate ventilation should be provided
PPE:	Rubber Gloves

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Low sheen, homogeneous emulsion
Binder:	Pure Acrylic Co Polymeric
Colour:	See Catalogue
SG:	1,2 - 1,24
KU:	119 - 125 @23Deg C
pH:	8,5 - 9,0
VOC:	Low VOC
Water Solubility:	Yes

10. STABILITY AND REACTIVITY

Stability:	No thermal decomposition if used correctly
Hazardous Decomposition products:	No hazards reaction if used correctly according to instructions

11. TOXICOLOGICAL DATA

- Skin:** No harmful effect
- Chronic:** No harmful effect
- Inhalation:** Fresh Air
- Oral:** Rinse with water, if vomiting occurs naturally seek medical assistance
- Carcinogenicity:** No Data available
- Mutagenicity:** No Data available
- Reproductive Hazard:** No Data available

12. ECOLOGICAL INFORMATION

May have short term impact, contain, clean, remove and monitor

13. DISPOSAL CONSIDERATIONS

Methods:	Collect, rinse and dispose in accordance with local regulations
-----------------	---

14. TRANSPORTATION INFORMATION

Road, rail and shipping. No UN classification as dangerous

15. REGULATORY INFORMATION

No Classification:	Avoid eye contact and ingestion Product contain biodegradable surfactants
---------------------------	--

16. OTHER INFORMATION

Communicate and familiarise the content of this MSDS to all personnel using the product

Although the product is non-hazardous, caution should be taken during application and storage. Keep container closed properly and away from children. Avoid contact with eyes, do not ingest. If ingested, drink plenty of water or milk, seek medical attention immediately. Refer to MSDS for complete information.

These recommendations are made as a result of testing and experience, it is believed to be true and in good faith. The manufacturer do not accept any liability pertaining the use of the product. It is the responsibility of the consumer to use the product in a safe manner. Please train and identify possible hazards pre-use.

ISSUED BY:	MW van der Westhuizen	SIGNED:	
-------------------	-----------------------	----------------	--