

TECHNICAL DATA SHEET

RCM RUBBER SEAL IT

PRODUCT CODE: RCM001

COMPILED DATE: 21 JUL 23 REVISE DATE: 21 JUL 25

PRODUCT DISCRIPTION

Low sheen multi purpose waterproofing coating

INTENDED APPLICATIONS

Waterproofing of most building substrates, encapsulation and corrosion protection.

PRODUCT FEATURES

UV resistant and reflective
Superior elongation properties
Easy to applicate and clean with no thinning
Superior adhesion to most building materials
Environmentally friendly with no solvents
Can be used with or without geotextile membranes
Low odour and safe for harvesting of water

TECHNICAL DATA

Appearance: Low sheen, homogeneous emulation

Binder: Pure Acrylic Co Polymeric

Colour: See Catalogue

SG: 1,2 - 1,24

KU: 119 - 125 @23Deg C

pH: 8,5 - 9,0

Recommended WFT: 1000 micron

VOC: Low VOC

Binder %: 65%

Chemical Resistance: Resistant to alkaline and acids spills at medium to high concentrations

UV Resistance: Passed Xenon QUV, start degrade after 5 years

APPLICATION DIRECTIVE

Mixing and Thinning: Single component, stir well before use. Do not dilute.

1 L per square meter, dependant on: Substrate (Profile and porosity) and application (with

Coverage: or without geotextile)

Environment: 10 to 30 Deg C, Max R Humidity 85%

Drying time before overcoat: 3 Hours @23 Deg C, R Humidity 50%

Substrate: Clean thoroughly, remove old unstable paint and waterproofing materials.

Treat all rusted areas if applicable.

Substrate must be dry.

Maintenance coats: 5 Years

TRANSPORTATION AND STORAGE

Transport: Classified as non-hazardous

Store: Store away from severe cold, heat and direct sun.

PACKAGING

Standard: 5L, 20L

SAFETY PRECAUTIONS

Although the product is non-hazardous, caution should be taken during application and storage. Keep container closed properly and away from children. Avoid contact with eyes, do not ingest. If ingested, drink plenty of water or milk, seek medical attention immediately. Refer to MSDS for complete information.

These recommendations are made as a result of testing and experience, it is believed to be true and in good faith. These directives do not imply any guarantee as the application and surface preparation methods is not within our control.







MATERIAL SAFETY DATA SHEET

PRODUCT CODE: RCM001

RCM RUBBER SEAL IT

COMPILED DATE: 21 JUL 23 REVISE DATE: 21 JUL 25

1. PRODUCT AND SUPPLIER IDENTIFICATION

Manufacturer: Rubber Coating Manufacturing Pty(Ltd)

Address: 62 Paterson rd., North End, Port Elizabeth, Eastern Cape, RSA

Contact details: 27 41 484 1569

marius@rubbercoating.co.za

Product use: Waterproofing Coating

Technical nature: Pure Acrylic Co Polymer based emulation used for a waterproofing coating

2. HAZARD IDENTIFICATION

Main Hazard: No great risk to health SAPMA rating 4 minimal

Contact Hazard Skin: Cat 2, may cause slight irritation

Eye: Cat 2, may cause slight irritation

Acute Toxicity Inhalation: No Data, Not Classified

Oral: Cat 2, may cause slight irritation *Dermal:* No Data available

Carcinogenicity: No Data available

Flammability: Non Flammable (Water based)

3. COMPOSITION INFORMATION

 CAS:
 W/W%

 Acrylic Polymer
 9003-63-840-60
 40-60

 Calcium Carbonate
 1317-65-3
 5-15

 Pigment
 N/A
 1-8

 Water
 7732-18-5
 20-30

4. FIRST AID MEASURES

Skin: Wash with water and dry
Eye: Rinse with water
Inhalation: Fresh Air

Oral: Rinse with water, if vomiting occurs naturally seek medical assistance

5. FIRE FIGHTING MEASURES

Extinguishing Media: Foam, CO2 or dry powder.

Hazard Contribution: Not flammable

6. ACCIDENTAL RELEASE MEASURES

PPE: Gloves,

Spill and Clean up method:

Clean with water and absorbing materials, disghard in accordance with local regulations

Environmental precaution: Contain, make sure that the product is not washed into pools, streams or sewer.

7. HANDLING AND STORAGE

Store in accordance with local regulations. Store away from severe cold, heat and direct sun. Keep container sealed and away from children.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Engineering Controls: Adequate ventilation should be provided

PPF: Rubber Gloves

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Low sheen, homogeneous emulation

Binder: Pure Acrylic Co Polymeric

Colour: See Catalogue

SG: 1,2 - 1,24

KU: 119 - 125 @23Deg C

pH: 8,5 - 9,0

voc: Low VOC

Water Solubility: Yes

10. STABILITY AND REACTIVITY

Stability: No thermal decomposition if used correctly

Hazardous Decomposition

ISSUED BY:

No hazards reaction if used correctly according to instructions products:

11. TOXICOLOGICAL DATA

Skin: No harmful effect Chronic: No harmful effect Inhalation: Fresh Air

Oral: Rinse with water, if vomiting occurs naturally seek medical assistance

Carcinogenicity: No Data available Mutagenicity: No Data available Reproductive Hazard: No Data available

12. ECOLOGICAL INFORMATION

May have short term impact, contain, clean, remove and monitor

13. DISPOSAL CONSIDERATIONS

Methods: Collect, rinse and dispose in accordance with local regulations

14. TRANSPORTATION INFORMATION

Road, rail and shipping. No UN classification as dangerous

15. REGULATORY INFORMATION

No Classification: Avoid eye contact and ingestion

Product contain biodegradable surfactants

16. OTHER INFORMATION

Communicate and familiarise the content of this MSDS to all personnel using the product

Although the product is non-hazardous, caution should be taken during application and storage. Keep container closed properly and away from children. Avoid contact with eyes, do not ingest. If ingested, drink plenty of water or milk, seek medical attention immediately. Refer to MSDS for complete information.

These recommendations are made as a result of testing and experience, it is believed to be true and in good faith. The manufacturer do not accept any liability pertaining the use of the product. It is the responsibility of the consumer to use the product in a safe manner. Please train and identify possible hazards pre-use.

SIGNED:

MW van der Westhuizen

